

Lambretta

E-BIKE



Lambretta
E-BIKE

FRAME
alloy

Rosario 28"

- Aluminium AL6061 T6 Hydro tubing
- HL-5955 HLO adjustable lockout travel 100mm
- Shimano DeoreT610 10 - speed
- Shimano Deore Disc BRM 615
- BOSCH Performance 250W
- BOSCH Performance 400 Wh (11 Ah)
- 20,4 Kg

www.lambrettaebikes.eu



BOSCH
Active Line



passione | tradizione | innovazione



www.lambrettaebikes.eu

FRAME
alloy

Roserio 28"

- Aluminium AL6061 T6 Hydro tubing
- HL-595S HLO adjustable lockout travel 100mm
- Shimano DeoreT610 10 - speed
- Shimano Deore Disc BRM 615
- BOSCH Performance 250W
- BOSCH Performance 400 Wh (11 Ah)
- 20,4 Kg



www.lambrettaebikes.eu

FRAME
alloy

Roserio 28"

- Aluminium AL6061 T6 Hydro tubing
- HL-595S HLO adjustable lockout travel 100mm
- Shimano DeoreT610 10 - speed
- Shimano Deore Disc BRM 615
- BOSCH Performance 250W
- BOSCH Performance 400 Wh (11 Ah)
- 20,4 Kg

FRAME
alloy

Roserio 28"

- Aluminium AL6061 T6 Hydro tubing
- HL-595S HLO adjustable lockout travel 100mm
- Shimano DeoreT610 10 - speed
- Shimano Deore Disc BRM 615
- BOSCH Performance 250W
- BOSCH Performance 400 Wh (11 Ah)
- 20,4 Kg

www.lambrettaebikes.eu



BOSCH
Active Line



FRAME alloy

Rosario 28"

- Aluminium AL6061 T6 Hydro tubing
- HL-595S HLO adjustable lockout travel 100mm
- Shimano DeoreT610 10 - speed
- Shimano Deore Disc BRM 61 S
- BOSCH Performance 250W
- BOSCH Performance 400 Wh (11 Ah)
- 20,4 Kg



passione | tradizione | innovazione

TECHNISCHE-DATEN

Rahmen / frame	Aluminium AL6061 T6 Hydro tubing	Aluminium AL6061 T6 Hydro tubing	Aluminium AL6061 T6
Gabel / fork	Aluminium RIGID Hydro form	Aluminium RIGID Hydro form	Adjustabel aluminium suspention fork
Steuersatz / headset	11/8"x1 1/5" tapered semi intergrated ahead	11/8"x1 1/5" tapered semi intergrated ahead	11/8"x1/5" tapered semi intergrated
Vorbau / stem	Ahead +/- 7° - extention 100mm	Ahead +/- 7° - extention 100mm	verstellbar / adjustable 0-60° - extention 80mm
Lenker / handlebar	Aluminium URBAN rise bar 5° 31.8" diameter	Aluminium URBAN rise bar 5° 31.8" diameter	Aluminium Trekking
Schaltung / shifting	Shimano DeoreT610 10-speed	Shimano DeoreT610 10-speed	Shimano Alfine 8-speed
Bremsen / brakes	Shimano Disc BRM355 (Front:180mm rotor; Rear:160mm rotor)	Shimano Disc BRM355 (Front:180mm rotor; Rear:160mm rotor)	Shimano Disc BRM355 (Front:180mm rotor; Rear:160mm rotor)
Reifen / tires	Schwalbe Super Moto X 62-584 - 27,5" Kevlar guard	Schwalbe Super Moto X 62-584 - 27,5" Kevlar guard	Schwalbe Energizer Life 40-622
Antrieb / drive system	BOSCH Active 250W	BOSCH Active 250W	BOSCH Active 250W
Batterie / battery	BOSCH Frame Type 400 Wh (11 Ah)	BOSCH Frame Type 400 Wh (11 Ah)	BOSCH Frame type 400 Wh (11 Ah)
Lauftradgröße / wheel size	27,5" - 62-584	27,5" - 62-584	28" - 40-622mm
Rahmengröße / frame size	50 cm /55 cm	45cm / 50 cm	48 cm / 53 cm
Gewicht / weight	22,5 Kg	22,5 Kg	26,5 Kg
Farbe / colour	Cool Grey Matt	Cool Grey Matt	Magic Black Matt

www.lambrettaebikes.eu

KSR Group GmbH

Gewerbeparkstrasse 11
A-3500 Krems a. d. Donau